





BAB9-63 Mini Circuit Breaker

► CONSTRUCTION AND FEATURE

- Convenient for sales in supermarket
- Locked or sealed protection cover to prevent from electricity stealing
- Protection against both overload and short circuit
- High short-circuit capacity
- Contact position indication
- Applicable to terminal and pin/fork type busbar connection
- Easy mounting onto 35mm DIN rail

► TECHNICAL DATA

- Pole No.: 1P, 2P, 3P, 4P
- Rated voltage: AC 230/400V
- Rated current (A): 1, 2, 3, 4, 5, 6, 8, 10, 13, 16, 20, 25, 32, 40, 50, 63
- Tripping curve: B,C,D
- Rated short-circuit capacity (Icn): 4500A
- Rated frequency: 50/60Hz
- Energy limiting class: 3
- Rated impulse withstand voltage: 6.2kV
- Electro-mechanical endurance: 4000
- Contact position indication
- Connection terminal:
 - Screw terminal
 - Pillar terminal with clamp
- Connection capacity: Rigid conductor up to 25mm²
- Fastening torque: 2.0Nm
- Installation:
 - On symmetrical DIN rail 35mm
 - Panel mounting
- Standards:
 - IEC/EN60898-1



Patent Protected

► OVERALL & INSTALLATION DIMENSIONS

